

TTS500-XS

UHF Reading Station for Textile Services Applications



HID's TTS500-XS is a UHF RFID 'smart' reading station designed to comply with laundry standards and environments. It offers a high read rate in a small footprint design, ideal for limited spaces. It is an all-in-one station featuring the most advanced RFID technologies, combined with a powerful microcomputer embedding HID's Acuity cloud-based linen management platform. TTS500-XS therefore eliminates the need for external gateways and keeps operating even in case of network connectivity loss. The station can also be remotely managed for configuration, monitoring and upgrades.

TTS500-XS can be used as a table-top station where space is limited, or as a wall-mounted station. It can also be affixed to custom metallic portal structures for bi-directional check-in/out control processes of RFID-enabled textile items.

An optical detector triggers reads of RFID-enabled items when required.



KEY BENEFITS:

- High-performance, compact UHF station
- Small in size and light weight
- Can be used as a table-top or wall-mounted station

For more information, contact tagsales@hidglobal.com

TTS500-XS


TECHNOLOGY HIGHLIGHTS:

- 865 to 928 MHz, EPC global C1 Gen 2, ISO 18000-63
- Network failure proof
- Can be remotely managed and upgraded

TYPICAL CONFIGURATIONS:

- Table-top
- Wall-mounted
- Portals and gate structures

TTS500-XS



Base Model Number	DDP16378 (EU version) DDP16525 (US version)
ELECTRONIC	
Operating Frequency	865-868 MHz (ETSI) 902-928 MHz (FCC)
Communication Interface	Ethernet 10/100
Transmit Power	5 dBm to 31.5 dBm (30 dBm max for US version)
Power Supply	12 VDC, 3A
Host Protocol	ACUITY Platform
PHYSICAL	
Dimensions	9 x 7.5 x 1.5 in (23 x 19 x 4 cm)
Weight	2.2 lbs (1 kg)
Casing	White casing, high-quality, scratch-resistant
THERMAL (AIR)	
Storage	-4° F to 158° F (-20°C to 70°C)
Operating	32° F to 130° F (0°C to 55°C)
OTHER	
Standards	EPC Global C1 Gen2, ISO/IEC18000-63
Additional Features	Optical detector to sense items placed on the surface 4 GPIOs, 3 external RF-ports (for additional antennas)



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +44 1440 714 850
Asia Pacific: +852 3160 9800 | Latin America: +52 (55) 9171-1108
For more global phone numbers click here

© 2022 HID Global Corporation/ASSA ABLOY AB. All rights reserved.
2022-03-02-idx-tts500-xs-ds-en-DRAFT PLT-06499
Part of ASSA ABLOY